




Minimum Evaporating Temp. With:

- 20 °C Suction Gas Return ASERCOM certified
- 25 °C Suction Gas Return with add cooling
- Maximum Evaporating Temperature
- 25 °C Suction Gas Return

Suction Return Temperature 20.0°C

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW									
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
20.0	43.30	55.90	71.10	89.10	110.50	135.00	163.50	196.50	233.00	249.00
25.0	39.70	51.70	66.10	83.20	103.00	126.50	153.50	184.00	219.00	234.00
30.0	36.00	47.50	61.10	77.10	95.90	117.50	143.00	171.50	204.00	219.00
35.0	32.40	43.20	56.00	70.90	88.40	108.50	132.00	159.00	189.50	203.00
40.0		38.90	50.80	64.70	80.90	99.60	121.50	146.00	174.50	187.00
45.0		34.60	45.60	58.30	73.20	90.40	110.00	133.00	159.50	170.50
50.0		30.20	40.30	51.90	65.40	81.00	99.00	120.00	143.50	154.00
55.0		25.90	35.00	45.40	57.50	71.50	87.60	106.50	128.00	137.50

50 Hz

D8SJ-600X

R404A Dew Point

Cond °C	Power, kW									
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
20.0	19.45	22.10	24.60	26.90	28.90	30.50	31.60	32.20	32.10	31.80
25.0	19.85	22.80	25.60	28.30	30.70	32.80	34.50	35.60	36.10	36.20
30.0	20.20	23.40	26.50	29.60	32.40	35.00	37.20	38.90	40.00	40.30
35.0	20.40	23.90	27.40	30.80	34.00	37.00	39.70	42.00	43.70	44.20
40.0		24.30	28.10	31.80	35.50	38.90	42.10	44.90	47.20	48.00
45.0		24.60	28.70	32.70	36.80	40.60	44.30	47.60	50.50	51.50
50.0		24.80	29.10	33.50	37.90	42.20	46.30	50.10	53.60	54.90
55.0		24.80	29.40	34.20	38.90	43.60	48.20	52.50	56.50	58.00

Cond °C	Current at 400 V, A									
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
20.0	50.05	52.64	55.35	58.00	60.42	62.44	63.87	64.54	64.28	63.88
25.0	50.43	53.37	56.51	59.68	62.69	65.38	67.58	69.10	69.76	69.76
30.0	50.77	54.04	57.60	61.27	64.88	68.24	71.18	73.54	75.13	75.51
35.0	51.02	54.63	58.60	62.76	66.94	70.97	74.66	77.84	80.35	81.12
40.0		55.10	59.47	64.12	68.88	73.56	77.98	81.99	85.40	86.55
45.0		55.43	60.20	65.33	70.65	75.97	81.13	85.95	90.25	91.79
50.0		55.60	60.76	66.36	72.23	78.20	84.08	89.70	94.89	96.81
55.0		55.58	61.12	67.19	73.61	80.20	86.79	93.21	99.29	101.58

Cond °C	Suction Mass Flow, g/s									
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
20.0	263.00	341.00	436.00	549.00	684.00	844.00	1032.00	1251.00	1506.00	1619.00
25.0	253.00	331.00	425.00	538.00	672.00	830.00	1015.00	1233.00	1486.00	1599.00
30.0	241.00	320.00	413.00	525.00	657.00	813.00	997.00	1212.00	1464.00	1577.00
35.0	229.00	307.00	400.00	510.00	641.00	795.00	977.00	1190.00	1440.00	1552.00
40.0		294.00	386.00	494.00	623.00	775.00	954.00	1165.00	1413.00	1525.00
45.0		279.00	370.00	477.00	603.00	752.00	929.00	1138.00	1385.00	1496.00
50.0		263.00	353.00	458.00	581.00	728.00	902.00	1109.00	1354.00	1465.00
55.0		246.00	334.00	437.00	558.00	702.00	874.00	1078.00	1324.00	1435.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	8
Displacement @ 50 Hz, m³/h	181
Bore/Stroke, mm	74.7/59.2
Length/Width, mm	835/527
Height, mm	610
Net Weight, kg	346
Gross Weight, kg	367
Suction, inch	3 1/8
Discharge, inch	1 5/8
Drive Frequency Range, Hz	25 - 60
Oil Quantity, l	7.6
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	457 x 305 (18)
Sound Pressure @ 1m, dBA	76
Sound Power, dBA	87
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	3922
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	114
Locked Rotor Current, A	476
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Deep Oil Sump	Mounted
Mounting Springs	4

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Capacity Control	Capacity Steps 75/50%
Discharge Temperature Protection	Head PTC sensor
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Enclosure Class	IP 56
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Crankcase Heater	200 W Internal

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
AWM	380-420 V / 3~ / 50 Hz	400	YY/Y	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
AWR	220-240 V / 3~ / 50 Hz	230	YY/Y	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YY/Y	Y	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YY/Y	Y	2.19
AWX	380 V / 3~ / 60 Hz	380	YY/Y	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YY/Y	Y	1.00