



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

1 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R134a

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	66925		kWh/a
Seasonal Energy Performance Ratio	SEPR	3,07		

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	33,5		kW
Rated power input	D _A	14,15		kW
Rated COP	COP _A	2,36		

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	36,6		kW
Declared power input	D _B	13,53		kW
Declared COP	COP _B	2,71		

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	41,0		kW
Declared power input	D _C	12,44		kW
Declared COP	COP _C	3,29		

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	45,1		kW
Declared power input	D _D	11,18		kW
Declared COP	COP _D	4,03		

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	28,5		kW
Declared power input	D _E	14,87		kW
Declared COP	COP _E	1,91		

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	to _H	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	C _{dc}	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems C_{dc} can not be determined by test. For this reason the default degradation coefficient C_{dc} (0.25) has to be applied according to EN 13215, Annex A.



Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R404A

Condensing unit with the selected refrigerant is only intended for evaporating temperatures below -15°C within the EU due to the legal requirements from the regulation (EU) 2015/1095. Permissible condensing unit-refrigerant combinations see Declaration of Conformity AC-500

Item	Symbol*	Value	Unit
Evaporating temperature	t	-35	°C
Annual electricity consumption	Q	75081	kWh/a
Seasonal Energy Performance Ratio	SEPR	1,87	

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	18,87	kW
Rated power input	D _A	13,42	kW
Rated COP	COP _A	1,41	

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	21,5	kW
Declared power input	D _B	13,27	kW
Declared COP	COP _B	1,62	

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	25,3	kW
Declared power input	D _C	12,83	kW
Declared COP	COP _C	1,97	

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	29,1	kW
Declared power input	D _D	12,15	kW
Declared COP	COP _D	2,39	

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	14,78	kW
Declared power input	D _E	13,32	kW
Declared COP	COP _E	1,11	

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

3 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28

Refrigerant: R407A

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q			kWh/a
Seasonal Energy Performance Ratio	SEPR			

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	Error: -4	Error: -4	kW
Rated power input	D _A			kW
Rated COP	COP _A			

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B			kW
Declared power input	D _B			kW
Declared COP	COP _B			

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C			kW
Declared power input	D _C			kW
Declared COP	COP _C			

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D			kW
Declared power input	D _D			kW
Declared COP	COP _D			

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E			kW
Declared power input	D _E			kW
Declared COP	COP _E			

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R407C

Condensing unit with the selected refrigerant is only intended for evaporating temperatures below -15°C within the EU due to the legal requirements from the regulation (EU) 2015/1095. Permissible condensing unit-refrigerant combinations see Declaration of Conformity AC-500

Item	Symbol*	Value		Unit
Evaporating temperature	t		-35	°C
Annual electricity consumption	Q			kWh/a
Seasonal Energy Performance Ratio	SEPR			

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A			kW
Rated power input	D _A			kW
Rated COP	COP _A			

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B			kW
Declared power input	D _B			kW
Declared COP	COP _B			

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C			kW
Declared power input	D _C			kW
Declared COP	COP _C			

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D			kW
Declared power input	D _D			kW
Declared COP	COP _D			

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E			kW
Declared power input	D _E			kW
Declared COP	COP _E			

Other items

Capacity control	—			
Reference temperature	Dew point temp.			
Suction gas temperature	toh		20°C	
Power voltage	Net		400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc		0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

5 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28

Refrigerant: R407F

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q			kWh/a
Seasonal Energy Performance Ratio	SEPR			

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	Error: -4	Error: -4	kW
Rated power input	D _A			kW
Rated COP	COP _A			

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B			kW
Declared power input	D _B			kW
Declared COP	COP _B			

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C			kW
Declared power input	D _C			kW
Declared COP	COP _C			

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D			kW
Declared power input	D _D			kW
Declared COP	COP _D			

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E			kW
Declared power input	D _E			kW
Declared COP	COP _E			

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

6 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R454C

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	101542	55177	kWh/a
Seasonal Energy Performance Ratio	SEPR	2,46	1,74	

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	40,6	12,91	kW
Rated power input	D _A	21,3	9,74	kW
Rated COP	COP _A	1,91	1,33	

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	45,2	14,74	kW
Declared power input	D _B	20,6	9,61	kW
Declared COP	COP _B	2,19	1,53	

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	51,5	17,53	kW
Declared power input	D _C	19,36	9,42	kW
Declared COP	COP _C	2,66	1,86	

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	57,8	20,4	kW
Declared power input	D _D	17,96	9,30	kW
Declared COP	COP _D	3,22	2,19	

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	--	--	kW
Declared power input	D _E	--	--	kW
Declared COP	COP _E	--	--	

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	to _H	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	C _{dc}	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems C_{dc} can not be determined by test. For this reason the default degradation coefficient C_{dc} (0.25) has to be applied according to EN 13215, Annex A.



Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R455A

Condensing unit with the selected refrigerant is only intended for evaporating temperatures below -15°C within the EU due to the legal requirements from the regulation (EU) 2015/1095. Permissible condensing unit-refrigerant combinations see Declaration of Conformity AC-500

Item	Symbol*	Value	Unit
Evaporating temperature	t	-35	°C
Annual electricity consumption	Q	57863	kWh/a
Seasonal Energy Performance Ratio	SEPR	1,59	

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	12,35	kW
Rated power input	D _A	10,50	kW
Rated COP	COP _A	1,18	

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	14,35	kW
Declared power input	D _B	10,39	kW
Declared COP	COP _B	1,38	

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	17,20	kW
Declared power input	D _C	10,16	kW
Declared COP	COP _C	1,69	

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	20,3	kW
Declared power input	D _D	9,93	kW
Declared COP	COP _D	2,04	

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	--	kW
Declared power input	D _E	--	kW
Declared COP	COP _E	--	

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	to _h	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	C _{dc}	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems C_{dc} can not be determined by test. For this reason the default degradation coefficient C_{dc} (0.25) has to be applied according to EN 13215, Annex A.



Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R507A

Condensing unit with the selected refrigerant is only intended for evaporating temperatures below -15°C within the EU due to the legal requirements from the regulation (EU) 2015/1095. Permissible condensing unit-refrigerant combinations see Declaration of Conformity AC-500

Item	Symbol*	Value	Unit
Evaporating temperature	t	-35	°C
Annual electricity consumption	Q	75239	kWh/a
Seasonal Energy Performance Ratio	SEPR	1,95	

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	19,67	kW
Rated power input	D _A	13,42	kW
Rated COP	COP _A	1,47	

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	22,4	kW
Declared power input	D _B	13,28	kW
Declared COP	COP _B	1,69	

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	26,3	kW
Declared power input	D _C	12,85	kW
Declared COP	COP _C	2,05	

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	30,3	kW
Declared power input	D _D	12,19	kW
Declared COP	COP _D	2,48	

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	15,41	kW
Declared power input	D _E	13,32	kW
Declared COP	COP _E	1,16	

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

9 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28

Refrigerant: R448A

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q			kWh/a
Seasonal Energy Performance Ratio	SEPR			

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	Error: -4	Error: -4	kW
Rated power input	D _A			kW
Rated COP	COP _A			

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B			kW
Declared power input	D _B			kW
Declared COP	COP _B			

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C			kW
Declared power input	D _C			kW
Declared COP	COP _C			

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D			kW
Declared power input	D _D			kW
Declared COP	COP _D			

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E			kW
Declared power input	D _E			kW
Declared COP	COP _E			

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R449A

Condensing unit with the selected refrigerant is only intended for evaporating temperatures below -15°C within the EU due to the legal requirements from the regulation (EU) 2015/1095. Permissible condensing unit-refrigerant combinations see Declaration of Conformity AC-500

Item	Symbol*	Value	Unit
Evaporating temperature	t	-35	°C
Annual electricity consumption	Q	64714	kWh/a
Seasonal Energy Performance Ratio	SEPR	1,80	

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	15,64	kW
Rated power input	D _A	11,50	kW
Rated COP	COP _A	1,36	

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	17,85	kW
Declared power input	D _B	11,35	kW
Declared COP	COP _B	1,57	

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	21,0	kW
Declared power input	D _C	11,03	kW
Declared COP	COP _C	1,90	

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	24,1	kW
Declared power input	D _D	10,58	kW
Declared COP	COP _D	2,28	

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	--	kW
Declared power input	D _E	--	kW
Declared COP	COP _E	--	

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	to _h	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	C _{dc}	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems C_{dc} can not be determined by test. For this reason the default degradation coefficient C_{dc} (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

11 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R450A

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	58626		kWh/a
Seasonal Energy Performance Ratio	SEPR	3,11		

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	29,7		kW
Rated power input	D _A	12,47		kW
Rated COP	COP _A	2,38		

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	32,5		kW
Declared power input	D _B	11,89		kW
Declared COP	COP _B	2,73		

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	36,4		kW
Declared power input	D _C	10,90		kW
Declared COP	COP _C	3,34		

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	40,0		kW
Declared power input	D _D	9,77		kW
Declared COP	COP _D	4,09		

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	25,2		kW
Declared power input	D _E	13,16		kW
Declared COP	COP _E	1,92		

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

12 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R513A

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	71304		kWh/a
Seasonal Energy Performance Ratio	SEPR	3,01		

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	34,9		kW
Rated power input	D _A	15,05		kW
Rated COP	COP _A	2,32		

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	38,4		kW
Declared power input	D _B	14,43		kW
Declared COP	COP _B	2,66		

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	43,1		kW
Declared power input	D _C	13,34		kW
Declared COP	COP _C	3,23		

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	47,7		kW
Declared power input	D _D	12,07		kW
Declared COP	COP _D	3,95		

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	29,5		kW
Declared power input	D _E	15,76		kW
Declared COP	COP _E	1,87		

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

13 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R1234yf

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	69251		kWh/a
Seasonal Energy Performance Ratio	SEPR	2,97		

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	33,4		kW
Rated power input	D _A	14,79		kW
Rated COP	COP _A	2,26		

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	36,8		kW
Declared power input	D _B	14,12		kW
Declared COP	COP _B	2,60		

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	41,5		kW
Declared power input	D _C	13,01		kW
Declared COP	COP _C	3,19		

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	45,9		kW
Declared power input	D _D	11,75		kW
Declared COP	COP _D	3,90		

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	28,0		kW
Declared power input	D _E	15,61		kW
Declared COP	COP _E	1,80		

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.



BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen

BITZER Software v6.18.0 rev2809

21.10.2025 / All data subject to change.

14 / 14

Performance Data Sheet according to EU Regulation 2015/1095

SEPR Declaration Model: LH135E/6HE-28Y

Refrigerant: R1234ze

Item	Symbol*	Value		Unit
Evaporating temperature	t	-10	-35	°C
Annual electricity consumption	Q	49944		kWh/a
Seasonal Energy Performance Ratio	SEPR	3,22		

Point A: Parameters at full load and ambient temperature 32°C

Rated cooling capacity	P _A	26,2		kW
Rated power input	D _A	10,63		kW
Rated COP	COP _A	2,46		

Point B: Parameters at part load and ambient temperature 25°C

Declared cooling capacity	P _B	28,6		kW
Declared power input	D _B	10,10		kW
Declared COP	COP _B	2,83		

Point C: Parameters at part load and ambient temperature 15°C

Declared cooling capacity	P _C	31,8		kW
Declared power input	D _C	9,23		kW
Declared COP	COP _C	3,45		

Point D: Parameters at part load and ambient temperature 5°C

Declared cooling capacity	P _D	34,9		kW
Declared power input	D _D	8,26		kW
Declared COP	COP _D	4,22		

Point E: Parameters at full load and ambient temperature 43°C (information only)

Declared cooling capacity	P _E	22,3		kW
Declared power input	D _E	11,27		kW
Declared COP	COP _E	1,98		

Other items

Capacity control	—		
Reference temperature	Dew point temp.		
Suction gas temperature	toh	20°C	
Power voltage	Net	400V/50Hz	
Coefficient of degradation for units w/o capacity control**	Cdc	0,25	

Additional document: [Declaration of Conformity AC-500](#)

Contact details:

BITZER Kühlmaschinenbau GmbH
Peter-Schaufler-Platz 1
71065 Sindelfingen
Deutschland
Tel +49 (0) 70 31 932-0
Fax +49 (0) 70 31 932-147
E-Mail: bitzer@bitzer.de
Internet: www.bitzer.de

* Symbols taken from english version of the Regulation 2015/1095

** Since condensing units are non functional systems Cdc can not be determined by test. For this reason the default degradation coefficient Cdc (0.25) has to be applied according to EN 13215, Annex A.